

CAP-150 Series – Capacitive Level Sensor

- ▶ For non-metallic containers
- Non-intrusive level sensing
- Optional Sight Glass Bracket
- Potentiometer for sensitivity adjustment

The CAP-150 series offers a unique level sensing solution for a wide variety of bottle types including plastic, glass and fiberglass. The non-contact sensor is ideally suited for medical applications such as waste, reagent or diluent liquids as well as dark, sticky or viscous fluids. The easy-to-calibrate sensor is available in both aqueous and non-aqueous versions and can be delivered with factory preset sensitivity for quick installation for OEM orders. The CAP-150 may also be used as a proximity sensor to detect the presence of solids such as pulp & paper.

Specifications

5 p com catrons					
Performance Nominal Sensing Distance, Sn	0.2' (5mm)				
	,				
Repeat Accuracy - (% of Sn)	<2%				
Hysteresis - (% of Sn)	<20%				
Mechanical					
Enclosure Ratings	IP67, NEMA 1,3,4,6,13				
Operating Temperature Range	-13°F to +158°F (-25°C to +70°C)				
LED Signal Indicator	Yellow				
Power On LED Indicator	Green				
Potentiometer	Yes				
Termination	78.74" (2 meter), 3 Wire PVC				
Shock	30g, 11ms				
Electrical					
Supply Voltage	5-48 VDC				
Continuous Switching Current	300 mA				
Voltage Drop	<2 VDC				
Current Consumption	<10 mA				
Switching Frequency	100 Hz, maximum				
Overload Protection	No				
Short Circuit	Yes				
Reverse Polarity Protection	Yes				
Approvals	CE				

How To Order

Select a Part Number based on Fluid Properties and Sink State.

Fluid Properties	Sensor Material	Flush Mountable	Sensing Range	Shielded	Sink/ Source	Logic	Part Number
Aqueous, Conductive (Unshielded Sensor)	Delrin® Body with Valox® Sensor Face	No	2-8mm	No	Sink	Wet	239890
						Dry	239891
					Source	Wet	241366
						Dry	241367
Non-Aqueous, Non-Conductive (Shielded Sensor)	Ni-Plated Brass Body with Valox® Sensor Face	Yes	1-5mm	Yes	Sink	Wet	240607
						Dry	240612
					Source	Wet	241368
						Dry	241369




Typical Applications

Fluid Monitoring:

- Waste
- Reagents
- Diluent
- Detergent/Wash
- Coolant
- Printing Ink

Dimensions



Wiring Diagram

Wet Sink Dry Sink 5-48VDC BRN 300mA max LOAD BLK BLU

Convert Simple Sight Glass into Switch Actuation Device

• For glass tubing 1/4" to 1" Dia.

Use this easy-to-install clamp with the CAP-150 to provide liquid level sensing and switch actuation along the length of sight glasses 1/4" to 1" in diameter.

Part Number: 240836

